

SOLAR INVERTERS

## ABB string inverters

UNO-DM-3.3/4.0/4.6/5.0-TL-PLUS-Q

3.3 to 5.0 kW



— UNO-DM-TL-PLUS-Q outdoor string inverter

### One size fits all

The design wraps ABB's quality and engineering into a lightweight and compact package thanks to technological choices optimized for installations with different orientation.

All power ratings share the same overall volume, allowing higher performance in a minimum space, and feature dual Maximum Power Point Trackers.

### Easy to install, fast to commission

The presence of Plug and Play connectors, both on the DC and AC side, as well as the wireless communication, enable a simple, fast and safe installation without the need of opening the front cover of the inverter.

The featured easy commissioning routine removes the need for a long configuration process, resulting in lower installation time and costs.

Improved user experience thanks to the build in User Interface (UI) or the Installer for Solar Inverters app which enable access to features such as advanced inverter configuration settings, dynamic feed-in control and load manager, from any WLAN enabled device (smartphone, tablet or PC).

### Smart capabilities

The embedded logging capabilities and direct transferring of the data to Internet (via Ethernet or WLAN) allow customers to enjoy the whole Aurora Vision® remote monitoring experience.

The UNO-DM-TL-PLUS-Q single-phase inverter family, with power ratings from 3.3 to 5.0 kW, is the optimal solution for residential installations.

The advanced communication interfaces (WLAN, Ethernet, RS485) combined with an efficient Modbus (RTU/TCP) communication protocol, Sunspec compliant, allow the inverter to be easily integrated within any smart environment and with third party monitoring and control systems. A complete set of control functions with the embedded efficient algorithm, enabling dynamic control of the feed-in (i.e. zero injection), make the inverter suitable for worldwide applications in compliance with regulatory norms and needs of the utilities.

### ABB Ability™ Energy Viewer for solar plants

This new tool allows residential customers to remotely monitor the performance of their own solar plant and provides all information necessary to increase energy self-reliance and self-sufficiency.

### Highlights

- Wireless access to the embedded Web User Interface
- Easy commissioning capability
- Future-proof with embedded connectivity for smart building and smart grid integration
- Dynamic feed-in control (for instance “zero injection”)
- Remote firmware upgrade for inverter and components
- Modbus TCP/RTU Sunspec compliant
- Lifetime free of charge access to Aurora Vision

# ABB string inverters


## UNO-DM-3.3/4.0/4.6/5.0-TL-PLUS-Q 3.3 to 5.0 kW



### Technical data and types

Type code	UNO-DM-3.3-TL-PLUS-Q	UNO-DM-4.0-TL-PLUS-Q	UNO-DM-4.6-TL-PLUS-Q	UNO-DM-5.0-TL-PLUS-Q
<b>Input side</b>				
Absolute maximum DC input voltage ( $V_{max,abs}$ )	600 V			
Start-up DC input voltage ( $V_{start}$ )	200 V (adj. 120...350 V)			
Operating DC input voltage range ( $V_{dcr,min}...V_{dcr,max}$ )	0.7 x $V_{start}...580$ V (min 90 V)			
Rated DC input voltage ( $V_{dcr}$ )	360 V			
Rated DC input power ( $P_{dcr}$ )	3500 W	4250 W	4750 W	5150 W
Number of independent MPPT	2			
Maximum DC input power for each MPPT ( $P_{MPPT,max}$ )	2000 W	3000 W	3000 W	3500 W
DC input voltage range with parallel configuration of MPPT at $P_{acr}$	170...530 V	130...530 V	150...530 V	170...480 V
DC power limitation with parallel configuration of MPPT $P_{acr}$	Linear derating from Max to Null [ $530V \leq V_{MPPT} \leq 580V$ ]	Linear derating from Max to Null [ $530V \leq V_{MPPT} \leq 580V$ ]	Linear derating from Max to Null [ $530V \leq V_{MPPT} \leq 580V$ ]	Linear derating from Max to Null [ $480V \leq V_{MPPT} \leq 580V$ ]
DC power limitation for each MPPT with independent configuration of MPPT at $P_{acr}$ , max unbalance example	2000 W [ $200 V \leq V_{MPPT} \leq 530 V$ ] the other channel: $P_{dcr} - 2000$ W [ $112 V \leq V_{MPPT} \leq 530 V$ ]	3000 W [ $190 V \leq V_{MPPT} \leq 530 V$ ] the other channel: $P_{dcr} - 3000$ W [ $90 V \leq V_{MPPT} \leq 530 V$ ]	3000 W [ $190 V \leq V_{MPPT} \leq 530 V$ ] the other channel: $P_{dcr} - 3000$ W [ $90 V \leq V_{MPPT} \leq 530 V$ ]	On MPPT 1: 3500 W [ $185 V \leq V_{MPPT} \leq 480 V$ ] On MPPT 2: $P_{dcr} - 3500$ W [ $145 V \leq V_{MPPT} \leq 480 V$ ] or 3500 W ( $305 V \leq V_{MPPT} \leq 480 V$ ) with no power on MPPT1
Maximum DC input current ( $I_{dcr,max}$ ) / for each MPPT ( $I_{MPPT,max}$ )	20.0/10.0 A	32.0/16.0 A	32.0/16.0 A	30.5/19-11.5 (MPPT 1 - MPPT 2)
Maximum input short circuit current for each MPPT	12.5 A	20.0 A	20.0 A	22.0 A
Number of DC input pairs for each MPPT	1			
DC connection type <sup>1)</sup>	Quick Fit PV Connector			
<b>Input protection</b>				
Reverse polarity protection	Yes, from limited current source			
Input over voltage protection for each MPPT-varistor	Yes			
Photovoltaic array isolation control	According to local standard			
DC switch rating for each MPPT (version with DC switch)	25 A / 600 V			
<b>Output side</b>				
AC grid connection type	Single-phase			
Rated AC power ( $P_{acr}@cos\phi=1$ )	3300 W	4000 W	4600 W	5000 W
Maximum AC output power ( $P_{ac,max}@cos\phi=1$ )	3300 W	4000 W <sup>2)</sup>	4600 W	5000 W
Maximum apparent power ( $S_{max}$ )	3300 VA	4000 VA <sup>2)</sup>	4600 VA	5000 VA
Rated AC grid voltage ( $V_{ac,r}$ )	230 V			
AC voltage range <sup>3)</sup>	180...264 V			
Maximum AC output current ( $I_{ac,max}$ )	14.5 A	17.2 A	20.0 A	22.0 A
Contributory fault current	16.0 A	19.0 A	22.0 A	24.0 A
Rated output frequency ( $f_r$ ) <sup>4)</sup>	50/60 Hz			
Output frequency range ( $f_{min}...f_{max}$ ) <sup>4)</sup>	47...53/57...63 Hz			
Nominal power factor and adjustable range	> 0.995, adj. $\pm 0.1 - 1$ (over/under excited)			
Total current harmonic distortion	< 3.5			
AC connection type	Female connector from panel			
<b>Output protection</b>				
Anti-islanding protection	According to local standard			
Maximum external AC overcurrent protection	20.0 A	25.0 A	25.0 A	32.0 A
Output overvoltage protection - varistor	2 (L - N / L - PE)			

ABB UNO-DM-3.3/4.0/4.6/5.0-TL-PLUS string inverter block diagram



Technical data and types

Type code	UNO-DM-3.3-TL-PLUS-Q	UNO-DM-4.0-TL-PLUS-Q	UNO-DM-4.6-TL-PLUS-Q	UNO-DM-5.0-TL-PLUS-Q
<b>Operating performance</b>				
Maximum efficiency ( $\eta_{max}$ )	97.0%	97.0%	97.0%	97.4%
Weighted efficiency (EURO/CEC)	96.5% / -	96.5% / -	96.5% / -	97.0% / -
Feed in power threshold	8 W			
Night consumption	<0.4 W			
<b>Embedded communication</b>				
Embedded communication interface <sup>5)</sup>	Wireless			
Embedded communication protocol	ModBus TCP (SunSpec)			
Commissioning tool	Web User Interface, Aurora Manager Lite			
Monitoring	Plant Portfolio Manager, Plant Viewer, Plant Viewer for Mobile, ABB Ability™ Energy Viewer for solar plants			
Optional board UNO-DM-COM kit				
Optional communication interface	RS485 (use with meter for dynamic feed-in control), Alarm/Load manager relay, Remote ON/OFF			
Optional communication protocol	ModBus RTU (SunSpec), Aurora Protocol			
Optional board UNO-DM-PLUS Ethernet COM kit				
Optional communication interface	Ethernet, RS485 (use with meter for dynamic feed-in control), Alarm/Load manager relay, Remote ON/OFF			
Optional communication protocol	ModBus TCP (SunSpec), ModBus RTU (SunSpec), Aurora Protocol			
<b>Environmental</b>				
Ambient temperature range	25...+60°C /-13...140°F with derating above 50°C/122°F	-25...+60°C /-13...140°F with derating above 50°C/122°F	-25...+60°C /-13...140°F with derating above 45°C/113°F <sup>6)</sup>	-25...+60°C /-13...140°F with derating above 45°C/113°F
Relative humidity	0...100 % condensing			
Maximum operating altitude without derating	2000 m / 6560 ft			
<b>Physical</b>				
Environmental protection rating	IP 65			
Cooling	Natural			
Dimension (H x W x D)	553 x 418 x 175 mm / 21.8" x 16.5" x 6.9"			
Weight	15 kg / 33 lbs			
Mounting system	Wall bracket			
<b>Safety</b>				
Isolation level	Transformerless			
Marking	CE, RCM			
Safety and EMC standard	IEC/EN 62109-1, IEC/EN 62109-2, AS/NZS 4777.2, EN 61000-6-1, EN 61000-6-2, EN 61000-6-3, EN 61000-6-4, EN 61000-3-11, EN 61000-3-12			
Grid standard (check your sales channel for availability) <sup>7)</sup>	CEI 0-21, DIN V VDE V 0126-1-1, VDE-AR-N 4105, G83/2, G59/3, RD 413, ITC-BT-40, AS/NZS 4777.2, C10/11, IEC 61727, IEC 62116			
<b>Available products variants</b>				
Standard	UNO-DM-3.3-TL-PLUS-B-Q	UNO-DM-4.0-TL-PLUS-B-Q	UNO-DM-4.6-TL-PLUS-B-Q	UNO-DM-5.0-TL-PLUS-B-Q
With DC switch	UNO-DM-3.3-TL-PLUS-SB-Q	UNO-DM-4.0-TL-PLUS-SB-Q	UNO-DM-4.6-TL-PLUS-SB-Q	UNO-DM-5.0-TL-PLUS-SB-Q

<sup>1)</sup> Refer to the document "String inverter – Product Manual appendix" available at [www.abb.com/solarinverters](http://www.abb.com/solarinverters) to know the brand and the model of the quick fit connector"

<sup>2)</sup> For UK G83/2 setting, maximum output current limited to 16 A up to a maximum output Pacr of 3600 W and a maximum apparent power of 3600 VA

<sup>3)</sup> The AC voltage range may vary depending on specific country grid standard

<sup>4)</sup> The Frequency range may vary depending on specific country grid standard;

CE is valid for 50Hz only

<sup>5)</sup> As per IEEE 802.11 b/g/n standard

<sup>6)</sup> Pacr = 4200 W @ 45°C/113°F

<sup>7)</sup> Further grid standard will be added, please refer to ABB Solar page for further details  
**Remark.** Features not specifically listed in the present data sheet are not included in the product

---

For more information please contact  
your local ABB representative or visit:

**[www.abb.com/solarinverters](http://www.abb.com/solarinverters)**  
**[www.abb.com](http://www.abb.com)**

---

We reserve the right to make technical  
changes or modify the contents of this  
document without prior notice. With  
regard to purchase orders, the agreed  
particulars shall prevail. ABB AG does not  
accept any responsibility whatsoever for  
potential errors or possible lack of  
information in this document.

We reserve all rights in this document and  
in the subject matter and illustrations  
contained therein. Any reproduction,  
disclosure to third parties or utilization of  
its contents – in whole or in parts – is  
forbidden without prior written consent of  
ABB AG. Copyright© 2018 ABB  
All rights reserved

