

# XS Series

Single MPPT, Single Phase



Technical Data	GW700-XS	GW1000-XS	GW1500-XS	GW2000-XS	GW2500-XS	GW3000-XS
<b>PV String Input Data</b>						
Max. DC Input Power (W)	910	1300	1950	2600	3250	3900
Max. DC Input Voltage (V)	500	500	500	500	500	500
MPPT Range (V)	40~450	40~450	50~450	50~450	50~450	50~450
Start-up Voltage (V)	40	40	50	50	50	50
Nominal DC Input Voltage (V)	360	360	360	360	360	360
Max. Input Current (A)	12.5	12.5	12.5	12.5	12.5	12.5
Max. Short Current (A)	15.6	15.6	15.6	15.6	15.6	15.6
No. of MPP Trackers	1	1	1	1	1	1
No. of Input Strings per Tracker	1	1	1	1	1	1
<b>AC Output Data</b>						
Nominal Output Power (W)	700	1000	1500	2000	2500	3000
Max. Output Apparent Power (VA)	770	1100	1650	2200	2750	3300
Nominal Output Voltage (V)	220/230	220/230	220/230	220/230	220/230	220/230
Nominal Output Frequency (Hz)	50/60	50/60	50/60	50/60	50/60	50/60
Max. Output Current (A)	3.5	4.8	7.2	9.6	12	14.3
Output Power Factor	~1 (Adjustable from 0.8 leading to 0.8 lagging)					
Output THDi (@Nominal Output)	<3%	<3%	<3%	<3%	<3%	<3%
<b>Efficiency</b>						
Max. Efficiency	97.2%	97.2%	97.3%	97.5%	97.6%	97.6%
European Efficiency	96.0%	96.4%	96.6%	97.0%	97.2%	97.2%
<b>Protection</b>						
Anti-islanding Protection	Integrated	Integrated	Integrated	Integrated	Integrated	Integrated
Input Reverse Polarity Protection	Integrated	Integrated	Integrated	Integrated	Integrated	Integrated
Insulation Resistor Detection	Integrated	Integrated	Integrated	Integrated	Integrated	Integrated
DC SPD Protection	Integrated	Integrated	Integrated	Integrated	Integrated	Integrated
AC SPD Protection	Integrated	Integrated	Integrated	Integrated	Integrated	Integrated
Residual Current Monitoring Unit	Integrated	Integrated	Integrated	Integrated	Integrated	Integrated
Output Over Current Protection	Integrated	Integrated	Integrated	Integrated	Integrated	Integrated
Output Short Protection	Integrated	Integrated	Integrated	Integrated	Integrated	Integrated
Output Over Voltage Protection	Integrated	Integrated	Integrated	Integrated	Integrated	Integrated
<b>General Data</b>						
Operating Temperature Range (°C)	-25~60	-25~60	-25~60	-25~60	-25~60	-25~60
Relative Humidity	0~100%	0~100%	0~100%	0~100%	0~100%	0~100%
Operating Altitude (m)	≤4000	≤4000	≤4000	≤4000	≤4000	≤4000
Cooling	Natural Convection					
User Interface	LCD & LED	LCD & LED	LCD & LED	LCD & LED	LCD & LED	LCD & LED
Communication	WiFi or LAN	WiFi or LAN	WiFi or LAN	WiFi or LAN	WiFi or LAN	WiFi or LAN
Weight (kg)	5.8	5.8	5.8	5.8	5.8	5.8
Size (Width*Height*Depth mm)	295*230*113	295*230*113	295*230*113	295*230*113	295*230*113	295*230*113
Protection Degree	IP65	IP65	IP65	IP65	IP65	IP65
Night Self Consumption (W)	<1	<1	<1	<1	<1	<1
Topology	Transformerless					
<b>Certifications &amp; Standards</b>						
Grid Regulation	VDE0126-1-1, EN50438 (PL), VDE4105, G98, AS/NZ S4777.2, CEI 0-21, UTE 15-712-1, RD1699+UNE, EN505049-1, IEC61727 IEC62116					
Safety Regulation	IEC62109-1&-2					
EMC	EN61000					