SOLARIA®

Solaria PowerXT[®] | DC Panel



Solaria PowerXT®-365R-PD

Achieving 20% efficiency, Solaria PowerXT solar panels are one of the highest power panels in the residential and commercial solar market. Compared to conventional panels, Solaria PowerXT panels have fewer gaps between the solar cells; this leads to higher power and superior aesthetics. Solaria PowerXT Pure Black[™] panels are manufactured with black backsheet and frames, enhancing a home or building's architectural beauty.

Developed in California, Solaria's patented cell cutting and panel assembly takes processed solar wafers and turns them into PowerXT solar panels. The process starts by creating a highly reliable PowerXT cell where busbars and ribbon interconnections are eliminated. Solaria then packages the cells into the PowerXT solar panel, reducing inactive space between the cells. This process leads to an exceptionally cost effective and efficient solar panel.

Higher Efficiency, Higher Power

Solaria PowerXT panels achieve up to 20.5% efficiency; conventional panels achieve 15% – 17% efficiency. Solaria PowerXT panels are one of the highest power panels available.

Lower System Costs

Solaria PowerXT panels produce more power per square meter area. This reduces installation costs due to fewer balance of system components.

Improved Shading Tolerance

Sub-strings are interconnected in parallel, within each of the four panel quadrants, which dramatically lowers the shading losses and boosts energy yield.

Improved Aesthetics

Compared to conventional panels, Solaria PowerXT panels have a more uniform appearance and superior aesthetics.

Durability and Reliability

Solder-less cell interconnections are highly reliable and designed to far exceed the industry leading 25 year warranty.



About Solaria

Established in 2000, The Solaria Corporation has created one of the industry's most respected IP portfolios, with over 250 issued and pending patents encompassing materials, processes, applications, products, manufacturing automation and equipment. Headquartered in Oakland, CA, Solaria has developed a technology platform that unlocks the potential of solar energy. Country of Manufacture: Korea

The Solaria Corporation Level 12, 469 La Trobe Street Victoria 3000 Australia | www.solaria.com/australia | Copyright © 2020 The Solaria Corporation Product specifications are subject to change without notice.

SOL∧RI∧°

| Performance at STC (1000W/m ² , 25° C, AM 1.5) | | | |
|---|---|---|--|
| Solaria PowerXT- Max Power (Pmax) Efficiency Open Circuit Voltage (Voc)* Short Circuit Current (lsc)* Max Power Voltage (Vmp) Max Power Current (Imp) Power Tolerance * Voc and lsc tolerance +/-5% | [W] [%] [V] [A] [V] [A] [%] | 365R-PD 365 20.2 48.0 9.58 39.9 9.16 -0/+3 | |
| Performance at NOCT (800W, | /m², 20°C Amb, Win | nd 1 m/s, AM 1.5) | |
| Max Power (Pmax) Open Circuit Voltage (Voc) Short Circuit Current (Isc) Max Power Voltage (Vmp) Max Power Current (Imp) | [W] [V] [A] [V] [A] | 269 45.1 7.73 36.7 7.32 | |
| Temperature Characteristic | S | | |
| NOCT Temp. Coeff. of P _{max} Temp. Coeff. of V _{oc} Temp. Coeff. of Isc | [°C] [% / °C] [% / °C] [% / °C] | 45 +/-2 -0.39 -0.29 0.04 | |
| Design Parameters | | | |
| Operating temperature Max System Voltage Max Fuse Rating Bypass Diodes | [°C] [V] [A] [#] | -40 to +85 1000 15 4 | |

IV Curves vs. Irradiance (370W Panel)

100% 98%

90%

80%



25-year Power, Parts and

Workmanship Limit

10

Years

Typical Tier

Solaria PowerXT®-365R-PD

| 5) | Mechanical Characteristic | 9 |
|--------------------|---|---|
| 2650.00 | | Monoorvetalling Silicon |
| 303K-PD | | |
| 303 | Dimensions (L X W X H) | 102111111 X 111011111 X 4011111 |
| 20.2 | Weight | ZIKG/40 IDS |
| 48.0 | Glass Type / Thickness | AR Coated, Tempered / 3.2mm |
| 9.58 | Frame Type | Black Anodised Aluminum |
| 39.9 | Cable Type / Length | 12 AWG PV Wire (UL) / 1000mm |
| 9.16 | Connector Type | Genuine MC4 |
| -0/+3 | (| (Male: PV-KST4, Female: PV-KBT4) |
| | Junction Box | IP67 / 4 diodes |
| nd 1 m/s. AM 1.5) | Front Test Load | 5400 Pa / 113 psf* |
| 269 | Rear Test Load | 3600 Pa / 75 psf* |
| 20J //5 1 | * Refer to Solaria Installation Manual for de | etails. 3600 Pa uplift is for bolted installation only. |
| 7 73 | Certifications / Warranty | |
| 36.7 | Certifications | IEC61215/61730 (ed. 2016) |
| 7.32 | | UL61730/CAN-CSA61730 |
| 1.02 | Fire Class (UL 790) | С |
| | Power Parts & Labor Warran | tv 25 vears* |
| 45 +/-2 | * Warranty details at www.solaria.com/au | stralia |
| -0.39 | Deckering | |
| -0.29 | Packaging | |
| 0.04 | Stacking Method | Horizontal / Palletised |
| 0.01 | Panels / Pallet | 25 |
| | Pallet Dimensions | 1668 x 1150 x 1230 mm |
| -40 to +85 | Pallet Weight | 590 kg / 1300 lbs |
| 1000 | Pallets / 40-ft Container | 28 |
| 15 | Panels / 40-ft Container | 700 |
| 4 | | |
| | [5.83in] | [63.62in] 1621mm [5.63in] |
| | [,98in] | + + + + + + + + + + + + + + + + + + + |
| | [43,94n] [11,8mm | |
| | NEGATIVE (-) 1000mm[39.37in] | _POSITIVE (+) 1000mm[39.37in] |
| 35 40 45 50 | Loging A B 1 | B A [35.43in] \$00mm 4X CROUND A |
| _abor from Solaria | | [2016] |
| industry warranty | | - [.39in] 10mm |
| | [.39in] | |
| | ĩ0mm - | |
| - 86% | [.28in] | 7 S [1.57in] 40mm |
| - 30% | 7mm | [.07in] |
| - 81% | | +k |
| | MOUNTING SLOT 'B' | |

The Solaria Corporation Level 12, 469 La Trobe Street Victoria 3000 Australia | www.solaria.com/australia | Copyright © 2020 The Solaria Corporation Product specifications are subject to change without notice.

20

35mm

FRAME PROFILE