


SOLAR'S MOST TRUSTED



# REC ALPHA 72 SERIES


450  
WP  
POWER



EXPERIENCE  
 $\alpha$   
PERFORMANCE

# REC ALPHA 72 SERIES

## PRODUCT DATASHEET



### GENERAL DATA

Cell type:	144 half-cut cells with REC heterojunction cell technology 6 strings of 24 cells in series	Connectors:	Stäubli MC4 Evo2 PV-KBT4-EVO-2/PV-KST4-EVO-2 (4 mm <sup>2</sup> ) in accordance with IEC 62852 IP68 only when connected
Glass:	3.2 mm solar glass with anti-reflection surface treatment	Cable:	4 mm <sup>2</sup> solar cable, 1.2 m + 1.3 m in accordance with EN 50618
Backsheet:	Highly resistant polymeric construction	Dimensions:	2063 x 1026 x 30 mm (2.12 m <sup>2</sup> )
Frame:	Anodized aluminum	Weight:	23.5 kg
Junction box:	3-part, 3 bypass diodes, IP67 rated in accordance with IEC 62790	Origin:	Made in Singapore

### ELECTRICAL DATA

Product Code\*: RECxxxAA 72

	430	435	440	445	450	
Power Output - P <sub>MAX</sub> (Wp)	430	435	440	445	450	
Watt Class Sorting - (W)	-0/+5	-0/+5	-0/+5	-0/+5	-0/+5	
Nominal Power Voltage - V <sub>MPP</sub> (V)	45.1	45.4	45.7	46.0	46.3	
STC	Nominal Power Current - I <sub>MPP</sub> (A)	9.54	9.59	9.63	9.68	9.72
	Open Circuit Voltage - V <sub>OC</sub> (V)	52.7	52.9	53.0	53.2	53.2
	Short Circuit Current - I <sub>SC</sub> (A)	10.25	10.27	10.31	10.38	10.43
Power Density (W/m <sup>2</sup> )	203.79	206.16	208.53	210.90	213.27	
Panel Efficiency (%)	20.4	20.6	20.8	21.0	21.3	
NMOT	Power Output - P <sub>MAX</sub> (Wp)	327	331	335	339	342
	Nominal Power Voltage - V <sub>MPP</sub> (V)	42.5	42.7	43.1	43.3	43.6
	Nominal Power Current - I <sub>MPP</sub> (A)	7.71	7.75	7.78	7.82	7.85
	Open Circuit Voltage - V <sub>OC</sub> (V)	49.7	49.8	49.9	50.1	50.1
Short Circuit Current - I <sub>SC</sub> (A)	8.28	8.29	8.33	8.38	8.42	

Values at standard test conditions (STC: air mass AM1.5, irradiance 1000 W/m<sup>2</sup>, temperature 25°C), based on a production spread with a tolerance of P<sub>MAX</sub>, V<sub>OC</sub> & I<sub>SC</sub> ±3% within one watt class.

Nominal module operating temperature (NMOT: air mass AM1.5, irradiance 800 W/m<sup>2</sup>, temperature 20°C, windspeed 1 m/s).

\*Where xxx indicates the nominal power class (P<sub>MAX</sub>) at STC above.

### CERTIFICATIONS

IEC 61215:2016, IEC 61730:2016, UL 1703

IEC 62804	PID
IEC 61701	Salt Mist
IEC 62716	Ammonia Resistance
ISO 11925-2	Ignitability (Class E)
IEC 62782	Dynamic Mechanical Load
IEC 61215-2:2016	Hailstone (35mm)
AS4040.2 NCC 2016	Cyclic Wind Load
ISO 14001:2004, ISO 9001:2015, OHSAS 18001:2007, IEC 62941	



### WARRANTY\*

	Standard	REC ProTrust	
Installed by an REC Certified Solar Professional	No	Yes	Yes
System Size	All	≤25 kW	25-500 kW
Product Warranty (yrs)	20	25	25
Power Warranty (yrs)	25	25	25
Labor Warranty (yrs)	0	25	10
Power in Year 1	98%	98%	98%
Annual Degradation	0.25%	0.25%	0.25%
Power in Year 25	92%	92%	92%

See warranty documents for details. Conditions apply.

### MAXIMUM RATINGS

Operational temperature:	-40 ... +85°C
Maximum system voltage:	1500 V
Design load (+): snow	3600 Pa (367 kg/m <sup>2</sup> )*
Maximum test load (+):	5400 Pa (550 kg/m <sup>2</sup> )*
Design load (-): wind	1600 Pa (163 kg/m <sup>2</sup> )*
Maximum test load (-):	2400 Pa (245 kg/m <sup>2</sup> )*
Max series fuse rating:	25 A
Max reverse current:	25 A

\* Calculated using a safety factor of 1.5  
\* See installation manual for mounting instructions


### TEMPERATURE RATINGS\*

Nominal Module Operating Temperature:	44°C (±2°C)
Temperature coefficient of P <sub>MAX</sub> :	-0.26 %/°C
Temperature coefficient of V <sub>OC</sub> :	-0.24 %/°C
Temperature coefficient of I <sub>SC</sub> :	0.04 %/°C

\*The temperature coefficients stated are linear values

### LOW LIGHT BEHAVIOUR

Typical low irradiance performance of module at STC:



REC Group is an international pioneering solar energy company dedicated to empowering consumers with clean, affordable solar power in order to facilitate global energy transitions. Committed to quality and innovation, REC offers photovoltaic modules with leading high quality, backed by an exceptional low warranty claims rate of less than 100ppm. Founded in Norway in 1996, REC employs 2,000 people and has an annual solar panel capacity of 1.8 GW. With over 10 GW installed worldwide, REC is empowering more than 16 million people with clean solar energy. REC Group is a Bluestar Elkem company with headquarters in Norway, operational headquarters in Singapore, and regional bases in North America, Europe, and Asia-Pacific.

**REC**  
www.recgroup.com

